Keep Turret Punch Press Tooling Sharp While Reducing Tool Inventory



Two Sizes for up to 5.0" and 6.3" Diameter Tooling

Hunton precision vertical grinders are ideal for all popular CNC tooling, including Amada, Behrens, Finn Power, Murata-Wiedemann, Raskin, Rhodes, Strippit and Trumpf.



425 Huehl Road, Northbrook, IL 60062 • (800)732-5289 • Fax: (847) 272-7948 www.foremostmachinery.com

OREMOST MACHINERY

HUNTON VERTICAL GRINDERS

- Sharpen punches and dies right at the workplace, quickly and easily.
- Drastically reduces tool room exchanges and tooling inventory.
- Tools sharpened regularly extend punch and die life, improve workpiece quality.
- Does the same work as expensive surface grinders at 1/3 the cost.
- Requires only a smooth swinging motion. Cast aluminum arm supported by dual thrust bearings.
- Convenient handwheel graduated in .001" increments provide fine feed and excellent finish.
- Complete with 3-jaw, shear grind or quick change chuck for punches; magnetic chuck for die buttons.
- Includes 5.0" or 6.3" straight cup grinding wheel specially formulated for turret press tooling.
- National sales and service through Foremost Machinery Corporation.



MODEL / SPECIFICATIONS

BG-90 (3-Jaw) **BG-90S** (Shear Grind)

1.2 HP, 3400 RPM **Electric Supply:** 220/440 Volt, 3 Phase, 60 Cycle

Maximum Clearance: over Magnetic Chuck over Jaws -

law Chuck: (with I/D and O/D Jaws) Hole in Chuck:

Magnetic Chuck: Grinding Wheel:

Bench Space: Weight:

Motor:

Standard Equipment:

3-1/2"

4"

5" Diameter 1-1/4" Diameter

4-3/4" Diameter 5.0" Diameter

18" x 16" 110 Lbs.

BG-790 (3-Jaw) **BG-790S** (Shear Grind) BG-790GT (Quick Change)

1.2 HP, 3400 RPM 220/440 Volt, 3 Phase, 60 Cycle

> 4-1/4" 4-1/4"

7" Diameter 1-7/8" Diameter

4-3/4" Diameter 6.3" Diameter

29" x 22" 280 Lbs.

3-Jaw, Shear Grind or Quick Change Chuck, Magnetic Chuck, Grinding Wheel, Diamond Tipped Dressing Stick, Dressing Stone. Coolant tank included with BG-790 Models.

COOLANT TANK



Coolant is recommended for sharpening large dies. The Coolant Tank has a moveable nozzle to provide coolant for both chucks. Tank is optional on the 5" models, standard on the 6.3" models.

QUICK CHANGE / SHEAR GRIND CHUCKS





CORPORATION

425 Huehl Road, Northbrook, IL 60062 • (800) 732-5289 • Fax: (847) 272-7948 www.foremostmachinery.com



SPECIFICATIONS

COOLANT TANK

Tank Capacity:	5 Gallons
Pump:	2.6 GPM
Electric Supply:	110 Volt AC 10 Watts
BG-90 Models	
Part No:	BG - CP
Size:	20" x 20"
Weight:	75 lbs.

BG-790 Models

(tank included with grinder) Size: 29" x 22"

SPECIFICATIONS

Angular Adjustment: 0 to 10 Degrees **Adjusting Screws: Right and Left Angle Locking Screws:** Right and Left Angle Includes "zero angle" pins for flat grinding and angle gauge.

QUICK CHANGE CHUCK

Holds assembled punches. Includes master holder and set of punch holders. Advise machine maker.

SHEAR GRIND CHUCK

Vee Block Capacity is 2" Dia. through Hole.

Distributed by:

CATALOG H-0996